

Features:

- Isolated mounting base 3000V~
- Pressure contact technology with increased power cycling capability
- Space and weight saving

Typical Applications:

- Various rectifiers
- DC supply for PWM inverter

V _{RRM}	Type & Outline
600V	MDx400-06-405F3
800V	MDx400-08-405F3
1000V	MDx400-10-405F3
1200V	MDx400-12-405F3
1400V	MDx400-14-405F3
1600V	MDx400-16-405F3
1800V	MDx400-18-405F3
1800V	MD400-18-405F3G

MDx stands for any type of MDC, MDA, MDK

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Single side cooled, T _c =60°C	150			400	A
I _{F(RMS)}	RMS forward current					628	A
I _{RRM}	Repetitive peak current	at V _{RRM}	150			30	mA
I _{FSM}	Surge forward current	V _R =60%V _{RRM} , t=10ms half sine.	150			13	kA
I ² t	I ² t for fusing coordination					845	10 ³ A ² s
V _{FO}	Threshold voltage		150			0.75	V
r _F	Forward slope resistance					0.64	mΩ
V _{FM}	Peak forward voltage	I _{FM} =1200A	25			1.65	V
R _{th(j-c)}	Thermal resistance Junction to case	Single side cooled per chip				0.16	°C/W
R _{th(c-h)}	Thermal resistance case to heatsink	Single side cooled per chip				0.04	°C/W
V _{iso}	Isolation voltage	50Hz, R.M.S, t=1min, I _{iso} :1mA(MAX)		3000			V
F _m	Terminal connection torque(M12)			12		14	N·m
	Mounting torque(M6)			4.5		6.0	N·m
T _{vj}	Junction temperature			-40		150	°C
T _{stg}	Stored temperature			-40		125	°C
W _t	Weight					1060	g
Outline	405F3						




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig.7





Fig.8

Outline:



Unmarked dimensional tolerance: ±0.5mm

