



Features:

- High short circuit capability, self limiting short circuit current
- Fast switching and short tail current
- Low switching losses
- 10kΩ Gate Protected Resistance Inside

Typical Applications:

- Inverter for Motor Drive
- High Power Converters
- Medical applications
- UPS systems

| SYMBOL | CHARACTERISTIC | TEST CONDITIONS | VALUE | | | UNIT |
|---------------|--|--|-------|------|-----------|-----------------------------|
| | | | Min | Type | Max | |
| V_{CES} | Collector-Emitter voltage | $T_j=25^{\circ}\text{C}$ | | | 600 | V |
| V_{GES} | Gate-Emitter voltage | $T_j=25^{\circ}\text{C}$ | | | ± 20 | V |
| I_C | Collector current | $T_c=60^{\circ}\text{C}$ | | | 600 | A |
| | | $T_c=25^{\circ}\text{C}$ | | | 720 | A |
| P_C | Collector power dissipation | $T_j=25^{\circ}\text{C}$, 1 device | | | 1650 | W |
| T_j | Junction temperature | / | | | 175 | $^{\circ}\text{C}$ |
| T_{stg} | Storage temperature | / | | | 125 | $^{\circ}\text{C}$ |
| V_{iso} | Isolation between terminal and copper base | $T_j=25^{\circ}\text{C}$, AC: 1minute | | | 3000 | V |
| Screw torque | Heatsink(M6) | / | | | 5 | N·m |
| | Terminals(M6) | / | | | 5 | N·m |
| | Terminals(M4) | / | | | 1.1 | N·m |
| I_{CES} | Zero gate voltage collector current | $T_j=25^{\circ}\text{C}$, $V_{CE}=600\text{V}$, $V_{GE}=0\text{V}$ | | | 1 | mA |
| I_{GES} | Gate-Emitter leakage current | $T_j=25^{\circ}\text{C}$, $V_{CE}=0\text{V}$, $V_{GE}=\pm 15\text{V}$ | | | ± 0.4 | μA |
| $V_{GE(th)}$ | Gate-Emitter threshold voltage | $T_j=25^{\circ}\text{C}$, $V_{CE}=V_{GE}$, $I_C=9.6\text{mA}$ | 4.9 | 5.8 | 6.5 | V |
| $V_{CE(sat)}$ | Collector-Emitter saturation voltage | $T_j=25^{\circ}\text{C}$, $V_{GE}=15\text{V}$, $I_C=600\text{A}$ | | 1.45 | 1.90 | V |
| | | $T_j=125^{\circ}\text{C}$, $V_{GE}=15\text{V}$, $I_C=600\text{A}$ | | 1.60 | | V |
| C_{ies} | Input capacitance | $T_j=25^{\circ}\text{C}$, $V_{CE}=25\text{V}$, $V_{GE}=0\text{V}$, $f=1\text{MHz}$ | | 37.2 | | nF |
| t_{on} | Turn-on time | $T_j=125^{\circ}\text{C}$, $V_{CC}=300\text{V}$, $I_C=100\text{A}$, $V_{GE}=\pm 15\text{V}$, $R_G=10\Omega$, Inductive load | | 290 | | ns |
| t_r | | | | 90 | | ns |
| t_{off} | | | | 520 | | ns |
| t_f | | | | 100 | | ns |
| V_F | Forward on voltage | $T_j=25^{\circ}\text{C}$, $I_F=600\text{A}$ | | 1.55 | 1.90 | V |
| | | $T_j=125^{\circ}\text{C}$, $I_F=600\text{A}$ | | 1.50 | | V |
| Q_{rr} | Reverse recovery charge | $T_j=125^{\circ}\text{C}$, $I_F=600\text{A}$, $di/dt=-6800\text{A}/\mu\text{s}$, $V_R=300\text{V}$ | | 50 | | μC |
| $R_{th(j-c)}$ | Thermal resistance(1 device) | IGBT | | | 0.09 | $^{\circ}\text{C}/\text{W}$ |
| Outline | 452H2 | | | | | |

Outline & Circuit Diagram

