



Features:

- n Center amplifying gate
- n Metal case with ceramic insulator
- n Low on-state and switching losses

Typical Applications:


- n AC controllers
- n DC and AC motor control
- n Controlled rectifiers

Part No. H89KPU-KT78dT

$I_{T(AV)}$	1500A
V_{DRM}, V_{RRM}	8000V
	8500V

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_j(^{\circ}C)$	VALUE			UNIT
				Min	Type	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Double side cooled	$T_c=70^{\circ}C$	115		1500	A
I_{DRM} I_{RRM}	Repetitive peak current	at V_{DRM} $t_p=10ms$ at V_{RRM} $t_p=10ms$	115			600	mA
I_{TSM}	Surge on-state current	10ms half sine wave $V_R=0.6V_{RRM}$	115			17	kA
I^2t	I^2t for fusing coordination					1445	10^3A^2s
V_{TO}	Threshold voltage		115			1.35	V
r_T	On-state slope resistance					0.53	$m\Omega$
V_{TM}	Peak on-state voltage	$I_{TM}=1500A, F=70kN$	25			2.00	V
dv/dt	Critical rate of rise of off-state voltage	$V_{DM}=0.67V_{DRM}$	115			2000	$V/\mu s$
di/dt	Critical rate of rise of on-state current	$V_{DM}=67\%V_{DRM}$, Gate pulse $t_r \leq 0.5\mu s$ $I_{GM}=1.5A$	115			200	$A/\mu s$
Q_{rr}	Recovery charge	$I_{TM}=2000A, t_p=4000\mu s, di/dt=-5A/\mu s,$ $V_R=50V$	115		5000		μC
I_{GT}	Gate trigger current			40		300	mA
V_{GT}	Gate trigger voltage	$V_A=12V, I_A=1A$	25	0.8		3.0	V
I_H	Holding current			25		200	mA
V_{GD}	Non-trigger gate voltage	$V_{DM}=67\%V_{DRM}$	115			0.3	V
$R_{th(j-c)}$	Thermal resistance Junction to case	Double side cooled				0.009	$^{\circ}C/W$
$R_{th(c-h)}$	Thermal resistance case to heatsink	Clamping force 70kN				0.002	
F_m	Mounting force			63	70	84	kN
T_{vj}	Junction temperature			-40		115	$^{\circ}C$
T_{stg}	Stored temperature			-40		140	$^{\circ}C$
W_t	Weight					1920	g
Outline	KT78dT						

Outline:



TECHSEM